Serial Number: 10/724,432 Filing Date: November 28, 2003

Title: HIGH EFFICIENCY SELF-CLEANING CENTRIFUGE

Page 4 Attorney Docket: 5039.001US1

IN THE CLAIMS

1. (Currently amended) A self-cleaning centrifuge for clarifying contaminated liquids comprising: [[, in part,]]

a rotor assembly supported for rotation about an axis, [[said]] the rotor assembly having a first set and a second set of nested first and second sets of cylinders each having a plurality of concentric cylinders, and with one of said sets being rotatably supported by the other of said sets and said cylinders having waste matter collection surfaces, each cylinder having one or more openings at a first end and one or more openings at an opposite second end, the cylinders defining a plurality of concentric liquid passageways configured for parallel unidirectional flow of the liquids through the plurality of concentric liquid passageways.

2-12. (Canceled)

- 13. (Currently amended) The centrifuge of claim 12 1, wherein said liquid passageway means includes interconnected radially and axially extending liquid passageway means wherein the plurality of concentric liquid passages extend from between the plurality of concentric cylinders in a radial manner and in an axial manner at a top and bottom of each cylinder.
- 14. (New) The centrifuge of claim 1, further comprising a brake operatively coupled to the first set of concentric cylinders to selectively brake the rotation of the first set relative to the second set.
- 15. (New) The centrifuge of claim 14, further comprising a bowl body operatively coupled to the rotor assembly and connected to one of the sets of cylinders, the bowl body having one or more bottom-positioned openings adapted to facilitate a passage of accumulated waste matter when the brake is applied.
- 16. (New) The centrifuge of claim 15, further comprising:

Serial Number: 10/724,432 Filing Date: November 28, 2003

Title: HIGH EFFICIENCY SELF-CLEANING CENTRIFUGE

Page 5 Attorney Docket: 5039.001US1

a sludge receptacle operatively coupled to receive purged waste from the self-cleaning centrifuge upon application of the brake; and

a clarified-liquid collection system operatively coupled to receive clarified liquid from an upper end of the bowl body during operation of the self-cleaning centrifuge.

17. (New) The centrifuge of claim 15, further comprising:

- a nozzle operatively coupled to supply the contaminated liquid to the plurality of concentric passages;
- a motor operatively coupled to rotate the plurality of concentric cylinders about the axis; and
 - a housing operatively coupled to hold the rotor assembly and the bowl body.
- 18. (New) The centrifuge of claim 1, wherein one of the sets is rotatably supported by the other of the sets, and wherein the cylinders have waste-matter collection surfaces.
- 19. (New) The centrifuge of claim 1, further comprising:
- a brake operatively coupled to the first set of concentric cylinders to selectively brake the rotation of the first set relative to the second set:
- a bowl body operatively coupled to the rotor assembly and connected to one of the sets of cylinders, the bowl body having one or more bottom-positioned openings adapted to facilitate a passage of accumulated waste matter when the brake is applied;
- a tube operatively coupled to supply the contaminated liquid to one end of the plurality of concentric liquid passages;
- a sludge collection system operatively coupled to receive purged waste from the selfcleaning centrifuge upon application of the brake:
- a clarified-liquid collection system operatively coupled to receive clarified liquid from an upper end of the bowl body during operation of the self-cleaning centrifuge;
- a motor operatively coupled to rotate the plurality of concentric cylinders about the axis; and
 - a frame operatively coupled to support the rotor assembly and the bowl body.

Serial Number: 10/724,432 Filing Date: November 28, 2003

Title: HIGH EFFICIENCY SELF-CLEANING CENTRIFUGE

Page 6 Attorney Docket: 5039.001US1

20. (New) The centrifuge of claim 1, further comprising a machine tool that uses a liquid to remove debris, the liquid and debris providing at least a portion of the contaminated liquids.

21. (New) A method comprising:

providing a centrifuge for clarifying contaminated liquids, the centrifuge including a rotor assembly supported for rotation about an axis, the rotor assembly having at least a first set and a second set of nested cylinders each having a plurality of concentric cylinders, each cylinder having one or more openings at a first end and one or more openings at an opposite second end, the cylinders defining a plurality of concentric liquid passageways;

supplying a liquid having components to be separated; and rotationally centrifuging the liquid using a unidirectional parallel concentric flow through the plurality of nested concentric cylindrical passageways.

- 22. (New) The method of claim 21, wherein the passing of the liquid includes introducing contaminated liquid in a radial manner at a first end of the nested concentric passageways and removing clarified liquid at an opposing second end of the nested concentric passageways.
- 23. (New) The method of claim 21, further comprising selectively braking a first set of concentric cylinders that define boundaries between the plurality of nested concentric cylindrical passageways in order to purge from accumulated waste from one or more surfaces of the first set of nested concentric cylinders.
- 24. (New) The method of claim 23, further comprising:

providing a bowl body surrounding the first set of nested concentric cylinders, the bowl body having an opening on the bottom of the bowl body; and

passing the purged accumulated waste through the opening on the bottom of the bowl.

25. (New) The method of claim 21, wherein the passing of the liquid includes:

Serial Number: 10/724,432

Filing Date: November 28, 2003

Title: HIGH EFFICIENCY SELF-CLEANING CENTRIFUGE

Page 7
Attorney Docket: 5039.001US1

2008/016

supplying contaminated liquid at a lower end of the plurality of nested concentric cylindrical passageways; and

removing clarified liquid from an upper end of the plurality of nested concentric cylindrical passageways.

26. (New) An apparatus comprising:

a frame;

means for rotationally centrifuging liquid about an axis in a unidirectional parallel concentric flow through a plurality of nested concentric cylindrical passageways, the means for rotationally centrifuging liquid supported by the frame.

27. (New) The apparatus of claim 26, wherein the means for rotationally centrifuging liquid include a first set and a second set of nested cylinders, each set having one or more concentric cylinders, each cylinder having means for removing accumulated waste sludge at a first end and means for removing clarified fluid at a second end, the cylinders defining the plurality of nested concentric cylindrical passageways configured for parallel unidirectional flow of the liquid.

28. (New) The apparatus of claim 26, wherein the means for removing accumulated waste sludge further include:

one or more openings at the first end of each cylinder; and

means for selectively braking the first set of concentric cylinders to loosen the sludge from the cylinders in order to have the sludge fall through the one or more openings at the first end of each cylinder.

- 29. (New) The apparatus of claim 27, further comprising means for rotating the first set and the second set of nested concentric cylinders about the axis; and means for rotatably connecting the plurality of concentric cylinders to the axis.
- 30. (New) The apparatus of claim 27, further comprising:

Scrial Number: 10/724,432 Filing Date: November 28, 2003

Title: HIGH EFFICIENCY SELF-CLEANING CENTRIFUGE

Page 8 Attorney Docket: 5039.001US1

means for containing the liquid around the sets of concentric cylinders during the rotationally centrifuging liquid about the axis, and wherein the means for removing accumulated waste sludge further includes means for emptying the means for containing the liquid.

31. (New) The apparatus of claim 26, further comprising:

means for supplying contaminated liquid into the means for centrifuging;

means for controlling the supplying of contaminated liquid to the rotor assembly;

means for collecting accumulated waste matter; and

means for collecting clarified liquid.